

PROFI LED BLOCK

Surface mounted direct lighting LED luminaire

Mounting:	Directly on the ceiling
Body material:	Aluminium profile
Colour:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Osram or equivalent LED stripe included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard, other on request
Driver:	Remote electronic driver in standard, DALI on request
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C... +40°C
IP Class:	IP20 in standard, IP44 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	N/A
Light distribution:	Symmetric
Diffuser:	White LED Block
General data:	3 Years standard warranty



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
6408.1500/830/1M	1500	14,4	3000K	Ra > 80	30.000	3	4	1000	0,40
6408.1500/840/1M	1500	14,4	4000K	Ra > 80	30.000	3	4	1000	0,40
6408.1500/860/1M	1500	14,4	6000K	Ra > 80	30.000	3	4	1000	0,40

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

