

**RONI LED/H**



Wall mounted IP65 LED luminaire.

|                                      |  |
|--------------------------------------|--|
| <b>Mounting:</b>                     | Directly on the wall   |
| <b>Body material:</b>                | Aluminium  |
| <b>Colour:</b>                       | Standard Dark Gray 7016, other RAL colours on request ( please add RAL code after index number ) |
| <b>LED module:</b>                   | Osram LED module included  |
| <b>Colour temperature:</b>           | 3000K or 4000K   |
| <b>Colour Rendering Index (CRI):</b> | >80 in standard  |
| <b>Driver:</b>                       | Electronic integrated driver   |
| <b>Emergency unit:</b>               | N/A  |
| <b>Movement sensor:</b>              | N/A  |
| <b>Daylight control sensor:</b>      | N/A  |
| <b>Operating temperature range:</b>  | - 20°C ... +40°C   |
| <b>IP Class:</b>                     | IP65   |
| <b>Power:</b>                        | 220-240V 50/60Hz   |
| <b>Lighting direction:</b>           | Direct   |
| <b>Reflector type:</b>               | N/A  |
| <b>Light distribution:</b>           | Symmetric  |
| <b>Diffusor:</b>                     | PMMA White diffusor  |
| <b>General data:</b>                 | 5 Years standard warranty  |

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



| Index no.     | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI     | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 4305.1500/830 | 1500              | 13        | 3000             | Ra > 80 | 50.000       | 5                | 3              | 1,80        |
| 4305.1500/840 | 1500              | 13        | 4000             | Ra > 80 | 50.000       | 5                | 3              | 1,80        |

