

COIN WALL 1



Wall mounted direct or direct / indirect IP54 LED luminaire.

Mounting:	Directly on the wall
Body material:	Aluminium
Colour:	Standard Dark Gray 7016, other RAL colours on request (please add RAL code after index number)
LED module:	Osram LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard
Driver:	Electronic integrated driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP54
Power:	220-240V 50/60Hz
Lighting direction:	Direct or direct / indirect
Reflector type:	Integrated lens
Reflector beam angle:	24° / 40°
Light distribution:	Symmetric
Diffusor:	Clear glass
General data:	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6286.2400/830/24	2400	32	3000	Ra > 80	35.000	5	4	3,90
6286.2400/840/24	2400	32	4000	Ra > 80	35.000	5	4	3,90
6286.2400/830/40	2400	32	3000	Ra > 80	35.000	5	4	3,90
6286.2400/840/40	2400	32	4000	Ra > 80	35.000	5	4	3,90
6286.3600/830/24	3600	46	3000	Ra > 80	35.000	5	4	3,90
6286.3600/840/24	3600	46	4000	Ra > 80	35.000	5	4	3,90
6286.3600/830/40	3600	46	3000	Ra > 80	35.000	5	4	3,90
6286.3600/840/40	3600	46	4000	Ra > 80	35.000	5	4	3,90

