

DUO SURF AR LED LV



Surface mounted LED luminaire.

| | |
|-------------------------------------|---|
| Mounting: | Directly on the ceiling |
| Body material: | Steel and aluminium |
| Colour: | Standard Gray RAL 9006, other RAL colours on request (please add RAL colour after index number) |
| LED module: | LED AR111 retrofit lamp included |
| Colour temperature: | 2700K or 3000K |
| Colour Rendering Index (CRI) | >80 in standard, other on request |
| Driver: | N/A |
| Emergency unit: | N/A |
| Movement sensor: | N/A |
| Daylight control sensor: | N/A |
| Operating temperature range: | 0°C ... +40°C |
| IP Class: | IP20 |
| Power: | 220-240V 50/60Hz |
| Lighting direction: | Direct lighting |
| Light distribution: | Symmetric |
| Beam angle: | 24° / 40° |
| General data: | 3 Years standard warranty |

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



| Index no. | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI | Lifetime [h] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|-------------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 3539.1220/827/24D | 1220 | 20 | 2700 | Ra > 80 | 40.000 | 3 | 3 | 2,60 |
| 3539.1220/830/40D | 1220 | 20 | 3000 | Ra > 80 | 40.000 | 3 | 3 | 2,60 |
| 3539.1600/827/24D | 1600 | 30 | 2700 | Ra > 80 | 40.000 | 3 | 3 | 2,60 |
| 3539.1520/827/40D | 1520 | 30 | 2700 | Ra > 80 | 40.000 | 3 | 3 | 2,60 |

