


OFFICE HD LED



Free standing floor LED luminaire with direct or direct / indirect lighting.

- Mounting:** Directly to the desk
- Body material:** Steel and aluminium
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips / Osram or Tridonic LED modules included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI)** >80 in standard, other on request
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct index nr. 6590.XXXX or Direct / indirect - index nr. 6590.UD.XXXX
- Reflector type:** N/A
- Light distribution:** Symmetric
- Diffuser:** Microprismatic [MPR] in standard, white acrylic diffuser [WD], acrylic frosted [AC] or any other diffuser on request
- General data:** 5 Years standard warranty
UGR<19 diffuser on request
Different lumen output or wattage available on request
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6590.4400/830	4400	29	3000	Ra > 80	50.000	5	3	9,00
6590.4400/840	4400	29	4000	Ra > 80	50.000	5	3	9,00
UP/DN								
6590.UD.8800/830	8800	57	3000	Ra > 80	50.000	5	3	9,00
6590.UD.8800/840	8800	57	4000	Ra > 80	50.000	5	3	9,00

