

## ECO LED HV 140




Recessed LED downlight for installation in suspended ceilings.

|                                     |  |
|-------------------------------------|--|
| <b>Mounting:</b>                    | Ceiling recessed, mounting brackets included   |
| <b>Body material:</b>               | Aluminium  |
| <b>Colour:</b>                      | Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)                           |
| <b>LED module:</b>                  | Philips / Osram / Tridonic LED module included   |
| <b>Colour temperature:</b>          | 3000K or 4000K   |
| <b>Colour Rendering Index (CRI)</b> | >80  |
| <b>Driver:</b>                      | Electronic integrated driver   |
| <b>Emergency unit:</b>              | N/A  |
| <b>Movement sensor:</b>             | N/A  |
| <b>Daylight control sensor:</b>     | N/A  |
| <b>Operating temperature range:</b> | 0°C ... +40°C  |
| <b>IP Class:</b>                    | IP44   |
| <b>Power:</b>                       | 220-240V 50/60Hz   |
| <b>Lighting direction:</b>          | Direct lighting  |
| <b>Reflector type:</b>              | Aluminium glossy   |
| <b>Light distribution:</b>          | Symmetric  |
| <b>Diffuser:</b>                    | Clear or frosted glass on request  |
| <b>General data:</b>                | 3 Years standard warranty  |
|                                     | All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist       |
|                                     | Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%. |
|                                     | System power consumption (LED module & driver) depends on components used  |

IP44 220-240 V  
50-60 Hz



| Index no.     | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI     | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 4273.1000/830 | 1000              | 13        | 3000             | Ra > 80 | 30.000       | 3                | 4              | 0,30        |
| 4273.1000/840 | 1000              | 13        | 4000             | Ra > 80 | 30.000       | 3                | 4              | 0,30        |



Ø 127