

**GARDEN MASTER LED**



Ground mounted IP65 LED luminaire.

- Mounting:** In the ground
- Body material:** Stainless steel & aluminium
- Colour:** Standard Anthracite grey 7016, other RAL colours on request (please add RAL code after index number)
- LED module:** LED GU10 retrofit lamp included
- Colour temperature:** 2700K, 3000K or 4000K available
- Colour Rendering Index (CRI):** >80 in standard, other on request
- Driver:** N/A
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** -20°C... +40°C
- IP Class:** IP65
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** N/A
- Light distribution:** Symmetric
- Diffuser:** Clear tempered glass in standard, mat on request
- General data:** 3 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5744.355/827/36D	355	4,6	2700	Ra > 80	15.000	3	4	0,90
5744.370/830/36D	370	4,6	3000	Ra > 80	15.000	3	4	0,90
5744.390/840/36D	390	4,6	4000	Ra > 80	15.000	3	4	0,90

