

**ECO PMF LED**


Pendant direct or direct / indirect LED luminaire.

<b>Mounting:</b>	Suspended on 1,5m long steel wire suspension ( with wire length control )
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Gray 9006, other RAL colours on request ( please add RAL code after index number )
<b>LED module:</b>	Philips / Osram or Tridonic LED module included
<b>Colour temperature:</b>	3000K or 4000K
<b>Colour Rendering Index (CRI)</b>	>80 in standard
<b>Driver:</b>	Electronic driver in standard, DALI on request
<b>Emergency unit:</b>	On request - Standard or DALI 3 hour emergency unit
<b>Movement sensor:</b>	on request
<b>Daylight control sensor:</b>	on request
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP20 in standard, IP44 on request
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting - index 6522 direct / indirect lighting - index 6550.UD
<b>Reflector type:</b>	Aluminium glossy or mat on request
<b>Light distribution:</b>	Symmetric
<b>Diffuser:</b>	Aluminium louver with acrylic insert
<b>General data:</b>	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux &amp; Luminaire Power tolerance +/- 10%.

System power consumption (LED module &amp; driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6522.8800/830	8800	57	3000	Ra > 80	50.000	5	3	4,80
6522.8800/840	8800	57	4000	Ra > 80	50.000	5	3	4,80
<b>UP/DN</b>								
6550.UD.13200/830	13200	86	3000	Ra > 80	50.000	5	3	4,80
6550.UD.13200/840	13200	86	4000	Ra > 80	50.000	5	3	4,80

