

GARDEN COIN LED



Ground mounted IP65 LED luminaire.

Mounting:	In the ground
Body material:	Stainless steel & aluminium
Colour:	Standard Anthracite grey 7016, other RAL colours on request (please add RAL code after index number)
LED module:	Osram LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic integrated driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting with possibility of light direction adjustment
Reflector type:	Integrated lenses
Light distribution:	Symmetric
Reflector beam angle:	24° / 40°
Diffuser:	Clear tempered glass in standard, mat on request
General data:	5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

IP65 220-240 V 50-60 Hz



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5743.1200/830/24	1200	16	3000	Ra > 80	35.000	5	4	1,10
5743.1200/840/24	1200	16	4000	Ra > 80	35.000	5	4	1,10
5743.1200/830/40	1200	16	3000	Ra > 80	35.000	5	4	1,10
5743.1200/840/40	1200	16	4000	Ra > 80	35.000	5	4	1,10
5743.1800/830/24	1800	23	3000	Ra > 80	35.000	5	4	1,10
5743.1800/840/24	1800	23	4000	Ra > 80	35.000	5	4	1,10
5743.1800/830/40	1800	23	3000	Ra > 80	35.000	5	4	1,10
5743.1800/840/40	1800	23	4000	Ra > 80	35.000	5	4	1,10

