

## FLAT PVS 600 LED



Recessed LED luminaire for installation in modular suspended ceilings, version for gypsum ceiling on request.

<b>Mounting:</b>	Modular ceiling lay in type in standard, mounting brackets for gypsum ceiling on request.
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Gray, other RAL colours on request (please add RAL colour after index number)
<b>LED module:</b>	Vossloh Schwabe LED module included
<b>Colour temperature:</b>	3000K or 4000K
<b>Colour Rendering Index (CRI)</b>	>80 in standard
<b>Driver:</b>	Electronic driver in standard, DALI on request
<b>Emergency unit:</b>	On request - Standard or DALI 3 hour emergency unit
<b>Movement sensor:</b>	on request
<b>Daylight control sensor:</b>	on request
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP44
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	Aluminium white
<b>Light distribution:</b>	Symmetric
<b>Diffuser:</b>	Altuglas [ ALT ] opalic diffusor
<b>General data:</b>	3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6195.3000/830	3000	30	3000	Ra > 80	50.000	3	4	3,50
6195.3000/840	3000	30	4000	Ra > 80	50.000	3	4	3,50
<b>UGR &lt; 19</b>								
6501.3300/830	3300	33	3000	Ra > 80	50.000	3	4	3,50
6501.3300/840	3300	33	4000	Ra > 80	50.000	3	4	3,50

