

GARDEN MINI LED



Ground mounted IP65 LED luminaire.

Mounting:	On the ground
Body material:	Stainless steel & aluminium
Colour:	Standard Anthracite grey 7016, other RAL colours on request (please add RAL code after index number)
LED module:	Philips / Osram or Tridonic LED module included
Colour temperature:	2700K, 3000K or 4000K available
Colour Rendering Index (CRI):	>80 in standard, other on request
Driver:	Electronic driver in standard
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	-20°C...+40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting with possibility of light direction adjustment
Reflector type:	Aluminium glossy
Light distribution:	Symmetric
Diffuser:	Clear tempered glass in standard, mat on request
General data:	5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3307.1100/827	1100	9	2700	Ra > 80	50.000	5	3	4,50
3307.1100/830	1100	9	3000	Ra > 80	50.000	5	3	4,50
3307.1100/840	1100	9	4000	Ra > 80	50.000	5	3	4,50
3307.2400/827	2400	20	2700	Ra > 80	50.000	5	3	4,50
3307.2400/830	2400	20	3000	Ra > 80	50.000	5	3	4,50
3307.2400/840	2400	20	4000	Ra > 80	50.000	5	3	4,50

