

METEOR 260 LED SQ



Ground mounted IP67 LED luminaire.

- Mounting:** In the ground
- Body material:** Stainless steel & aluminium
- Colour:** Stainless steel ring, body standard black RAL 9005
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 2700K, 3000K or 4000K available
- Colour Rendering Index (CRI):** >80 in standard, other on request
- Driver:** Electronic driver in standard
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** -20°C ... +40°C
- IP Class:** IP67
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct
- Reflector type:** Aluminium glossy
- Light distribution:** Symmetric
- Diffuser:** Clear tempered glass in standard, mat on request
- General data:** 5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6545.2400/827	2400	20	2700	Ra > 80	50.000	5	3	6,40
6545.2400/830	2400	20	3000	Ra > 80	50.000	5	3	6,40
6545.2400/840	2400	20	4000	Ra > 80	50.000	5	3	6,40
6545.3200/827	3200	28	2700	Ra > 80	50.000	5	3	6,40
6545.3200/830	3200	28	3000	Ra > 80	50.000	5	3	6,40
6545.3200/840	3200	28	4000	Ra > 80	50.000	5	3	6,40
6545.4500/830	4500	34	3000	Ra > 80	50.000	5	3	6,40
6545.4500/840	4500	34	4000	Ra > 80	50.000	5	3	6,40

