# PLAFO 1500 LED PND

**Please see the attached pages for detailed specifications.**



Direct/indirect version

| | |
|---|---|
| **Mounting:** | Pendant |
| **Body material:** | Steel & Aluminium |
| **Colour:** | Grey RAL9006 |
| **LED module:** | First brand LED module |
| **Colour temperature:** | 3000k/4000k |
| **Colour Rendering Index (CRI):** | CRI 80> |
| **Driver:** | First brand driver |
| **Emergency unit:** | Yes |
| **Movement sensor:** | Available on request |
| **Daylight control sensor:** | Available on request |
| **Operating temperature range:** | 0°c to +40°c |
| **IP Class:** | IP20 |
| **Power:** | 220-240V 50/60Hz |
| **Lighting direction:** | Direct |
| **Reflector type:** | Aluminium White |
| **Light distribution:** | Symmetric |
| **Diffuser:** | White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request. |
| **General data:** | 5 Years standard warranty, possible extension with project registration<br>Different lumen output or wattage available on request<br>All other technical features such as : Luminaire Eicacy, LOR, Lumen maintenance L/B etc. available in our pricelist<br>Wattage of products may vary due to constant LED eicacy improvements. Luminous lux & Luminaire Power tolerance +/- 10%.<br>System power consumption (LED module & driver) depends on components used |

25 Romer Street, Bolton
BL2 6BG
Tel: 01204 867727
www.marliteuk.co.uk