

COIN TUBE



LED spotlight for three - phase track systems.

Mounting:	Directly in 3 phase track
Body material:	Steel and aluminium
Colour:	Standard Gray RAL 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Osram LED module included
Colour temperature:	2700 K, 3000K or 4000K
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic driver, DALI on request
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting with possibility of light direction adjustment
Reflector type:	Integrated lens
Light distribution:	Symmetric
Reflector beam angle:	24° / 40°
Diffuser:	N/A
General data:	5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Ceiling mounting base instead of Track Adaptor available on request

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3409.2400/827/24D	2400	24	2700	Ra > 80	50.000	5	4	1,80
3409.2400/830/24D	2400	24	3000	Ra > 80	50.000	5	4	1,80
3409.2400/840/24D	2400	24	4000	Ra > 80	50.000	5	4	1,80
3409.2400/827/40D	2400	24	2700	Ra > 80	50.000	5	4	1,80
3409.2400/830/40D	2400	24	3000	Ra > 80	50.000	5	4	1,80
3409.2400/840/40D	2400	24	4000	Ra > 80	50.000	5	4	1,80
3409.3600/827/24D	3600	35	2700	Ra > 80	50.000	5	4	1,80
3409.3600/830/24D	3600	35	3000	Ra > 80	50.000	5	4	1,80
3409.3600/840/24D	3600	35	4000	Ra > 80	50.000	5	4	1,80
3409.3600/827/40D	3600	35	2700	Ra > 80	50.000	5	4	1,80
3409.3600/830/40D	3600	35	3000	Ra > 80	50.000	5	4	1,80
3409.3600/840/40D	3600	35	4000	Ra > 80	50.000	5	4	1,80

