

## **GLOWER LED**



IP20 $\frac{220.240  V}{50.40  Hz}$ F $(\pm)$ CE	

Index no.	Lumen output [Im]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4746.100/830	100	3	3000	Ra > 80	30.000	3	3	0,20

Wall mounted LED luminaire

Mounting:				
Body material:				

Colour:

LED module:

- Colour temperature:
- Colour Rendering Index (CRI):
- Driver:
- Emergency unit:
- Movement sensor:
- Daylight control sensor: Operating temperature
- range:

IP Class:

- Power:
- Lighting direction:

Reflector type: Light distribution:

General data:

N/A Symmetric

Wall recessed

Steel and aluminium

LED module included

Electronic driver included

2700K

>80

N/A

N/A

N/A

IP20

Direct

0°C ... +40°C


220-240V 50/60Hz

Standard White RAL 9016, other RAL colours on request ( please add RAL code after index number )

3 Years standard warranty Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.





25 Romer Street, Bolton BL2 6BG Tel: 01204 867727 www.marliteuk.co.uk