

PLAFON 2



Surface mounted LED luminaire.

Mounting:	Directly on the ceiling
Body material:	Aluminium and PMMA
Colour:	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
LED module:	Osram LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard
Driver:	Electronic driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP44 in standard, IP54 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	Aluminium white
Light distribution:	Symmetric
Diffuser:	white PMMA
General data:	3 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6506.700/830	700	9	3000	Ra > 80	30.000	3	4	1,20
6506.700/840	700	9	4000	Ra > 80	30.000	3	4	1,20

