

DUO FIX MINI


Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5879.2200/827	2200	18	2700	Ra > 80	50.000	5	3	2,50
5879.2200/830	2200	18	3000	Ra > 80	50.000	5	3	2,50
5879.2200/840	2200	18	4000	Ra > 80	50.000	5	3	2,50
5879.2200/927	2200	22	2700	Ra > 90	50.000	5	3	2,50
5879.2200/930	2200	22	3000	Ra > 90	50.000	5	3	2,50
5879.2200/940	2200	22	4000	Ra > 90	50.000	5	3	2,50

Recessed LED downlight for installation in suspended ceilings.

Mounting:	Ceiling recessed, mounting brackets included
Body material:	Aluminium
Colour:	Standard Black RAL 9005, other RAL colours on request (please add RAL colour after index number)
LED module:	Philips / Osram / Tridonic or equivalent LED module included
Colour temperature:	3000K or 4000K in standard other on request
Colour Rendering Index (CRI)	>80 or >90 available
Driver:	Electronic driver in standard, DALI or 1-10V Analogue on request
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting with possibility of light direction adjustment
Reflector type:	Aluminium glossy
Light distribution:	Symmetric
Diffuser:	Clear or frosted glass on request
General data:	5 Years standard warranty Different lumen output or wattage available on request All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%. System power consumption (LED module & driver) depends on components used

