

**CONO 1**



Pendant LED luminaire

- Mounting:** Suspended on 1,5m long wire suspension
- Body material:** Steel and aluminium
- Colour:** Standard Gray 9006, other RAL colours on request ( please add RAL code after index number )
- LED module:** LED GU10 retrofit lamp included
- Colour temperature:** 2700K , 3000K or 4000K available
- Colour Rendering Index (CRI):** >80 in standard, other on request
- Driver:** N/A
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** N/A
- Light distribution:** Symmetric
- Reflector beam angle:** 36° other on request
- General data:** 3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



| Index no.        | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI     | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|------------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 4586.355/827/36D | 355               | 4,6       | 2700             | Ra > 80 | 15.000       | 3                | 4              | 0,40        |
| 4586.370/830/36D | 370               | 4,6       | 3000             | Ra > 80 | 15.000       | 3                | 4              | 0,40        |
| 4586.390/840/36D | 390               | 4,6       | 4000             | Ra > 80 | 15.000       | 3                | 4              | 0,40        |

