

MIRROR V


Wall mounted LED mirror

Mounting:	Wall mounted
Body material:	Steel, aluminium and glass
Colour:	Standard Gray RAL 9006, other RAL colours on request (please add RAL code after index number)
LED module:	LED modules included
Colour temperature:	3000K
Colour Rendering Index (CRI):	>80
Driver:	Electronic driver included
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP44
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	N/A
Light distribution:	Symmetric
General data:	3 Years standard warranty

Available version with heating mat behind the mirror to prevent fog - HM in index number

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

IP44

 220-240 V
50-60 Hz


Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5915.3600/830	3600	40	3000	Ra > 80	30.000	3	3	15,00
5915.3600/830/HM	3600	80	3000	Ra > 80	30.000	3	3	15,00

