

MAG 66



Recessed LED luminaire for installation in modular suspended ceilings, version for gypsum ceiling on request.

- Mounting:

Modular ceiling lay in type in standard, mounting brackets for gypsum ceiling on request.
- Body material:

Steel and aluminium
- Colour:

Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
- LED module:

Philips / Osram or Tridonic LED module included
- Colour temperature:

3000K or 4000K
- Colour Rendering Index (CRI)

>80 in standard, >90 on request
- Driver:

Electronic driver in standard, DALI on request
- Emergency unit:

On request - Standard or DALI 3 hour emergency unit
- Movement sensor:

on request
- Daylight control sensor:

on request
- Operating temperature range:

0°C ... +40°C
- IP Class:

IP20
- Power:

220-240V 50/60Hz
- Lighting direction:

Direct / indirect lighting
- Reflector type:

White painted
- Light distribution:

Symmetric
- Diffuser:

Microprismatic [MPR] diffusor in standard
- General data:

5 Years standard warranty
- Different lumen output or wattage available on request
- All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
- Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
- System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6502.4400/830	4400	29	3000	Ra > 80	50.000	5	3	5,00
6502.4400/830	4400	29	4000	Ra > 80	50.000	5	3	5,00

