PLAFO 1250 LED

Please see the attached pages for detailed specifications.



Direct/indirect version

Mounting:	Surface
Body material:	Steel & Aluminium
Colour:	Grey 9006
LED module:	First brand LED module
Colour temperature:	3000k/4000k
Colour Rendering Index (CRI):	CRI 80>
Driver:	First brand driver
Emergency unit:	Yes
Movement sensor:	Available on request
Daylight control sensor:	Available on request
Operating temperature range:	0°c to +40°c
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	Aluminium White
Light distribution:	Symmetric
Diffuser:	White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.
General data:	5 Years standard warranty, possible extension with project registration Different lumen output or wattage available on request All other technical features such as : Luminaire Eicacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED eicacy improvements. Luminous lux & Luminaire Power tolerance +/- 10%. System power consumption (LED module & driver) depends on components used

25 Romer Street, Bolton
BL2 6BG
Tel: 01204 867727
www.marliteuk.co.uk