

DLK 155 SURF



Surface mounted LED luminaire.

- Mounting:** Directly on the ceiling
- Body material:** Steel and aluminium
- Colour:** Standard Gray RAL 9006, other RAL colours on request (please add RAL colour after index number)
- LED module:** Philips or Osram LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard
- Driver:** Electronic integrated driver in standard, DALI on request
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP44
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.
- General data:** 5 Years standard warranty
Different lumen output or wattage available on request
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5788.1100/830	1100	10	3000	Ra > 80	50.000	5	3	2,50
5788.1100/840	1100	10	4000	Ra > 80	50.000	5	3	2,50
5788.2000/830	2000	18	3000	Ra > 80	50.000	5	3	2,50
5788.2000/840	2000	18	4000	Ra > 80	50.000	5	3	2,50

