

PROFI 60 H WLX LED



Available versions



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
6599.4400/830	4400	30	3000	Ra > 80	50.000	5	3	587	3,00
6599.4400/840	4400	30	4000	Ra > 80	50.000	5	3	587	3,00
6599.6600/830	6600	46	3000	Ra > 80	50.000	5	3	868	4,00
6599.6600/840	6600	46	4000	Ra > 80	50.000	5	3	868	4,00
6599.8800/830	8800	58	3000	Ra > 80	50.000	5	3	1149	5,00
6599.8800/840	8800	58	4000	Ra > 80	50.000	5	3	1149	5,00
6599.11000/830	11000	72	3000	Ra > 80	50.000	5	3	1430	7,00
6599.11000/840	11000	72	4000	Ra > 80	50.000	5	3	1430	7,00

Wall mounted direct / indirect LED luminaire

- Mounting:** Directly on the wall
- Body material:** Aluminium profile
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI)** >80 in standard, other on request
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct / indirect
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.
- General data:** 5 Years standard warranty

UGR<19 diffuser on request
Luminaires can be connected into long lighting lines
Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist


Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

[WD] diffuser



[AC] diffuser



[MPR] diffuser

