

T-POOLE



T shaped Aluminium Profile lighting system. Height of the vertical bar or length of lighting runs can be customized.

- Mounting:** Vertical bar is mounted to the floor, Horizontal bar is suspended, standard 1,5 m steel wire suspensions included
- Body material:** Aluminium profile
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips / Osram / Tridonic or equivalent LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard , other on request
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C ... +40°C
- UGR:** UGR<19
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** Microprismatic [MPR] in standard other on request
- General data:** 5 Years standard warranty

Different lumen output or wattage available on request


All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6539.16500/830	16500	108	3000K	Ra > 80	50.000	5	3	19,00
6539.16500/830	16500	108	4000K	Ra > 80	50.000	5	3	19,00



Power outlets can be placed in the construction elements.