


PLAFO LOW 430 LED

Surface mounted LED luminaire.

- Mounting:** Directly on the ceiling
- Body material:** Steel and aluminium
- Colour:** Standard Gray RAL 9006, other RAL colours on request (please add RAL colour after index number)
- LED module:** Philips / Osram / Tridonic or equivalent LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.
- General data:** 5 Years standard warranty



| Index no. | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 6567.4200/830 | 4200 | 34 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 3,50 |
| 6567.4200/840 | 4200 | 34 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 3,50 |



Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used