

FIVE WALL LED



Wall mounted IP65 LED luminaire.

- Mounting:** Directly on the wall
- Body material:** Aluminium and steel
- Colour:** Standard Gray RAL 9006 other RAL colours on request (please add RAL code after index number)
- LED module:** Osram or Tridonic LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard
- Driver:** Electronic integrated driver in standard, DALI on request
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** - 20°C ... +40°C
- IP Class:** IP65
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct
- Reflector type:** N/A
- Light distribution:** Symetric
- Diffusor:** White PMMA Acrylic diffusor in standard, Microprismatic [MPR] or any other on request
- General data:** 5 Years standard warranty

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4926.2500/830	2500	18	3000	Ra > 80	50.000	5	3	6,90
4926.2500/840	2500	18	4000	Ra > 80	50.000	5	3	6,90

