

INDUSTRIAL LED


Pendant LED luminaire.

Mounting:	Suspended on 1,5m long steel chain suspension
Body material:	Steel and aluminium
Colour:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Philips / Osram or Tridonic LED module included
Colour temperature:	3000K or 4000K available
Colour Rendering Index (CRI)	>80 or >90 in standard
Driver:	Electronic driver in standard, DALI on request
Emergency unit:	On request - Standard or DALI 3 hour emergency unit
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C... +40°C
IP Class:	IP44
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	Aluminium white
Light distribution:	Symmetric
General data:	5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6525.12800/830	12800	112	3000	Ra > 80	50.000	5	3	15,00
6525.12800/840	12800	112	4000	Ra > 80	50.000	5	3	15,00
6525.18000/830	18000	144	3000	Ra > 80	50.000	5	3	15,00
6525.18000/840	18000	144	4000	Ra > 80	50.000	5	3	15,00

