

**DUO SLM**




Recessed LED downlight for installation in suspended ceilings.

- Mounting:** Ceiling recessed, mounting brackets included
- Body material:** Steel and aluminium
- Colour:** Standard Gray 9006 / Black RAL 9005, other RAL colours on request (please add RAL colour after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 2700K, 3000K or 4000K
- Colour Rendering Index (CRI):** >80 or >90 in standard
- Driver:** Electronic driver in standard, DALI or 1-10V Analogue on request
- Emergency unit:** On request - Standard or DALI 3 hour emergency unit
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** Aluminium glossy
- Light distribution:** Symmetric
- Reflector beam angle:** 16° / 24° / 36° / 54°

- Diffuser:** Clear or frosted glass on request
- General data:** 5 Years standard warranty, possible extension with project registration
- Different lumen output or wattage available on request
- Product is also available with special application LED modules: Premium Color, CrispWhite,
- Food WarmWhite, Food PremiumRed and many others - details on request
- All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
- Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
- System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3048.2200/827	2200	18	2700	Ra > 80	50.000	5	3	3,80
3048.2200/830	2200	18	3000	Ra > 80	50.000	5	3	3,80
3048.2200/840	2200	18	4000	Ra > 80	50.000	5	3	3,80
3048.4800/827	4800	40	2700	Ra > 80	50.000	5	3	3,80
3048.4800/830	4800	40	3000	Ra > 80	50.000	5	3	3,80
3048.4800/840	4800	40	4000	Ra > 80	50.000	5	3	3,80
3048.6400/827	6400	56	2700	Ra > 80	50.000	5	3	3,80
3048.6400/830	6400	56	3000	Ra > 80	50.000	5	3	3,80
3048.6400/840	6400	56	4000	Ra > 80	50.000	5	3	3,80
3048.2200/927	2200	22	2700	Ra > 90	50.000	5	3	3,80
3048.2200/930	2200	22	3000	Ra > 90	50.000	5	3	3,80
3048.2200/940	2200	22	4000	Ra > 90	50.000	5	3	3,80
3048.4000/927	4000	40	2700	Ra > 90	50.000	5	3	3,80
3048.4000/930	4000	40	3000	Ra > 90	50.000	5	3	3,80
3048.4000/940	4000	40	4000	Ra > 90	50.000	5	3	3,80
3048.6000/927	6000	64	2700	Ra > 90	50.000	5	3	3,80
3048.6000/930	6000	64	3000	Ra > 90	50.000	5	3	3,80
3048.6000/940	6000	64	4000	Ra > 90	50.000	5	3	3,80
3048.6000/930CW	6000	72	3000	Ra > 90	50.000	5	3	3,80
3048.5200/925FW	5200	70	2500	Ra > 90	50.000	5	3	3,80
3048.5200/930FR	5200	70	3000	Ra > 90	50.000	5	3	3,80



255x140