

## WL LED CUBE



Wall mounted direct / indirect LED luminaire

<b>Mounting:</b>	Wall mounted
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard White 9010, other RAL colours on request
<b>LED module:</b>	LED module included
<b>Colour temperature:</b>	3000K
<b>Colour Rendering Index (CRI):</b>	>80
<b>Driver:</b>	Electronic driver
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C... +40°C
<b>IP Class:</b>	IP20
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct / indirect
<b>Reflector type:</b>	N/A
<b>Light distribution:</b>	Symmetric
<b>General data:</b>	3 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4592.320/830	320	4	3000	Ra > 80	30.000	3	4	0,40

