

**TRE SLM**



Recessed LED downlight for installation in suspended ceilings.

- Mounting:** Ceiling recessed, mounting brackets included
- Body material:** Steel and aluminium
- Colour:** Standard Gray 9006 / Black RAL 9005, other RAL colours on request (please add RAL colour after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 2700K, 3000K or 4000K
- Colour Rendering Index (CRI):** >80 or >90 in standard
- Driver:** Electronic driver in standard, DALI or 1-10V Analogue on request
- Emergency unit:** On request - Standard or DALI 3 hour emergency unit
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** Aluminium glossy
- Light distribution:** Symmetric
- Reflector beam angle:** 16° / 24° / 36° / 54°
- Diffuser:** Clear or frosted glass on request
- General data:** 5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

Product is also available with special application LED modules: Premium Color, CrispWhite,

Food WarmWhite, Food PremiumRed and many others - details on request


All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3049.3300/827	3300	27	2700	Ra > 80	50.000	5	3	5,30
3049.3300/830	3300	27	3000	Ra > 80	50.000	5	3	5,30
3049.3300/840	3300	27	4000	Ra > 80	50.000	5	3	5,30
3049.7200/827	7200	60	2700	Ra > 80	50.000	5	3	5,30
3049.7200/830	7200	60	3000	Ra > 80	50.000	5	3	5,30
3049.7200/840	7200	60	4000	Ra > 80	50.000	5	3	5,30
3049.9600/827	9600	84	2700	Ra > 80	50.000	5	3	5,30
3049.9600/830	9600	84	3000	Ra > 80	50.000	5	3	5,30
3049.9600/840	9600	84	4000	Ra > 80	50.000	5	3	5,30
3049.3300/927	3300	33	2700	Ra > 90	50.000	5	3	5,30
3049.3300/930	3300	33	3000	Ra > 90	50.000	5	3	5,30
3049.3300/940	3300	33	4000	Ra > 90	50.000	5	3	5,30
3049.6000/927	6000	60	2700	Ra > 90	50.000	5	3	5,30
3049.6000/930	6000	60	3000	Ra > 90	50.000	5	3	5,30
3049.6000/940	6000	60	4000	Ra > 90	50.000	5	3	5,30
3049.9000/927	9000	96	2700	Ra > 90	50.000	5	3	5,30
3049.9000/930	9000	96	3000	Ra > 90	50.000	5	3	5,30
3049.9000/940	9000	96	4000	Ra > 90	50.000	5	3	5,30
3049.9000/930CW	9000	108	3000	Ra > 90	50.000	5	3	5,30
3049.7800/925FW	7800	105	2500	Ra > 90	50.000	5	3	5,30
3049.7800/930FR	7800	105	3000	Ra > 90	50.000	5	3	5,30



375x140

