

CALISIA 600





Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]	
6090.4800/827	4800	54	2700	Ra > 80	50.000	5	4	5,90	

Pendant LED luminaire.

Colour:

Suspended on 1,5m long steel wire suspension (with wire length control) Mounting:

Body material: Steel and aluminium

> Standard Black 9005, other RAL colours on request (please add RAL code after index

number)

LED module: Philips retrofit E27 LED bulb

Colour temperature: 2700K

Colour Rendering Index (CRI)

>80 in standard

Driver: N/A N/A Emergency unit: Movement sensor: N/A Daylight control sensor: N/A

Operating temperature range:

0°C ... +40°C

IP Class: IP20

Power: 220-240V 50/60Hz Lighting direction: Direct lighting

Reflector type: N/A Light distribution: Symmetric

General data: 3 Years standard warranty

> Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



